



TEST REPORT

Report No.: G7932.01-901-44

Rendered to:

VPI QUALITY WINDOWS Spokane, Washington

PRODUCT TYPE: PVC Casement Window

SERIES/MODEL: Endurance 511

SPECIFICATIONS:

AAMA/WDMA/CSA 101/I.S.2/A440-11, NAFS 2011 - North American Fenestration Standard/Specification for Windows, Doors, and Skylights and

AAMA/WDMA/CSA 101/I.S.2/A440-08, NAFS - North American Fenestration Standard/Specification for Windows, Doors, and Skylights and

CSA A440S1-09, Canadian Supplement to AAMA/WDMA/CSA 101/I.S.2/A440, NAFS - North American Fenestration Standard/Specification for Windows, Doors, and Skylights

	Summary of Results	
Title	Test Specimen #1 Standard W/S	Test Specimen #2 Mclaren W/S
AAMA/WDMA/CSA 101/I.S.2/A440-08 and -11	Class-CW-PG50 Size tested: 915 x 1830 (36 x 72)-Type C	Class-CW-PG50 Size tested: 915 x 1830 (36 x 72)-Type C
Design Pressure	±2400 Pa (50.13 psf)	±2400 Pa (50.13psf)
Air Infiltration	<0.05 L/s/m ² (<0.01 cfm/ft ²)	<0.05 L/s/m ² (<0.01 cfm/ft ²)
Air Exfiltration	<0.05 L/s/m ² (<0.01 cfm/ft ²)	<0.05 L/s/m ² (<0.01 cfm/ft ²)
Canadian Air Infiltration/Exfiltration Level	A3	А3
Water Penetration Resistance Test Pressure	360 Pa (7.52 psf)	360 Pa (7.52 psf)

Test Completion Date: 02/17/17

Reference must be made to Report No. G7932.01-901-44, dated 02/23/17 for complete test specimen description and detailed test results.