

TEST REPORT FOR VPI QUALITY WINDOWS

Report No.: N3980.01-901-44

REPORT ISSUED TO

VPI QUALITY WINDOWS

3420 E. Ferry Avenue
Spokane, Washington 99202

SECTION 1

SCOPE

Architectural Testing, Inc. (an Intertek company) dba Intertek Building & Construction (B&C) was contracted by VPI Quality Windows to perform testing in accordance with AAMA/WDMA/CSA 101/I.S.2/A440 on their ID 355 - Endurance - PW - 48" x 72". Results obtained are tested values and were secured by using the designated test method(s). Testing was conducted at the Intertek B&C test facility in Kent, Washington.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. Intertek B&C will service this report for the entire test record retention period. The test record retention period ends ten years after the test date. Test records, such as detailed drawings, datasheets, representative samples of test specimens, or other pertinent project documentation, will be retained for the entire test record retention period.

Unless differently required, Intertek reports apply the "Simple Acceptance" rule, also called "Shared Risk approach," of ILAC-G8:09/2019, Guidelines on Decision Rules and Statements of Conformity.

For INTERTEK B&C:

COMPLETED BY:	Arbind Raj	REVIEWED BY:	Jacob McDaniel
TITLE:	Laboratory Supervisor	TITLE:	Technician
SIGNATURE:	 Digitally Signed by: Arbind Raj	SIGNATURE:	 Digitally Signed by: Jacob McDaniel
DATE:	03/21/22	DATE:	03/21/22

AR/JM:pac

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT FOR VPI QUALITY WINDOWS

Report No.: N3980.01-901-44

SECTION 2

SUMMARY OF TEST RESULTS

TITLE	RESULTS
AAMA/WDMA/CSA 101/I.S.2/A440-17	Class LC – PG50 Size Tested 1219 x 1829 mm (48 x 72 in)* – Type FW
Design Pressure	±2400 Pa (±50.13 psf)
Air Infiltration	0.1 L/s/m ² (0.01 cfm/ft ²)
Air Exfiltration	0.2 L/s/m ² (0.04 cfm/ft ²)
Canadian Air Infiltration/Exfiltration Level	Fixed
Cyclic Water Penetration Resistance Test Pressure	360 Pa (7.52 psf)

Reference must be made to Intertek B&C Report No. N3980.01-901-44, dated 03/21/22 for complete test specimen description and detailed test results.

**Reference Intertek B&C Report No. M2278.01-901-44, dated 05/25/21 for complete Gateway test specimen description and test results.*

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.