



TEST REPORT

Report No.: F3982.02-901-44

Rendered to:

VPI QUALITY WINDOWS Spokane, Washington

PRODUCT TYPE: PVC Fixed Window **SERIES/MODEL**: Endurance

SPECIFICATIONS:

AAMA/WDMA/CSA 101/I.S.2/A440-11, NAFS 2011 - North American Fenestration Standard/Specification for Windows, Doors, and Skylights and

AAMA/WDMA/CSA 101/I.S.2/A440-08, NAFS - North American Fenestration Standard/Specification for Windows, Doors, and Skylights

and

CSA A440S1-09, Canadian Supplement to AAMA/WDMA/CSA 101/I.S.2/A440, NAFS - North American Fenestration Standard/Specification for Windows, Doors, and Skylights

Title	Summary of Results
AAMA/WDMA/CSA 101/I.S.2/A440-08 and -11	Class CW PG40 1830 x 2438 (72 x 96) Type FW
Design Pressure	±1920 Pa (40.10 psf)
Air Infiltration	<0.01 L/s/m ² (<0.01 cfm/ft ²)
Air Exfiltration	<0.01 L/s/m ² (<0.01 cfm/ft ²)
Canadian Air Infiltration/Exfiltration Level	Fixed
Water Penetration Resistance Test Pressure	720 Pa (15.04 psf)

Test Completion Date: 01/08/16

Reference must be made to Report No. F3982.02-901-44, dated 02/23/16 for complete test specimen description and detailed test results.