



**TEST REPORT**

**Report No.:** G9229.01-901-44

**Rendered to:**

VPI QUALITY WINDOWS  
Spokane, Washington

**PRODUCT TYPE:**

PVC Composite Window Assembly  
incorporating a Horizontal Sliding Window (XOX) over Fixed/Fixed/Fixed

**SERIES/MODEL:** Endurance

**SPECIFICATIONS:**

AAMA/WDMA/CSA 101/I.S.2/A440-11, *NAFS 2011 - North American Fenestration Standard/Specification for Windows, Doors, and Skylights*

and

AAMA/WDMA/CSA 101/I.S.2/A440-08, *NAFS - North American Fenestration Standard/Specification for Windows, Doors, and Skylights*

and

CSA A440S1-09, Canadian Supplement to AAMA/WDMA/CSA 101/I.S.2/A440, *NAFS - North American Fenestration Standard/Specification for Windows, Doors, and Skylights*

<b>Title</b>	<b>Summary of Results</b>
AAMA/WDMA/CSA 101/I.S.2/A440-08 and -11	Class LC PG50 2745 x 2438 (108 x 96) Type HS
Design Pressure	±2400 Pa (50.13 psf)
Air Infiltration	0.26 L/s/m <sup>2</sup> (0.05 cfm/ft <sup>2</sup> )
Air Exfiltration	0.22 L/s/m <sup>2</sup> (0.04 cfm/ft <sup>2</sup> )
Canadian Air Infiltration/Exfiltration Level	A3
Water Penetration Resistance Test Pressure	360 Pa (7.52 psf)

**Test Completion Date:** 03/29/17

Reference must be made to Report No. G9229.01-901-44, dated 04/27/17 for complete test specimen description and detailed test results.