


**NOTE: PLEASE VERIFY ALL HEAD AND SILL HEIGHTS. VPI defines the Rough Opening (RO) as the clear opening after all installation and waterproofing materials are applied. It is critical that the RO is a minimum of 1/2" larger than the net window frame size for nail flange applications. In the event that your VPI product will be installed with strap anchors, the RO must be 1" larger than the net frame size of the window. VPI shall not be responsible for any incorrect RO sizes.**




**VPI QUALITY WINDOWS**  
 3420 E. Terry Ave.  
 Spokane, WA 99202  
 www.vpiwindows.com


NAIL FIN - NF




**EXTERIOR ELEVATIONS**




1. LC-PG30 (108 X 66) END OX
2. LC-PG40 (96 X 63) END XO
3. LC-PG50 (71 X 56) END XO




4. LC-PG30 (108 X 66) END XO
5. LC-PG30 (144 X 72) END XO
6. LC-PG50 (120 X 60) END XO



7. LC-PG25 (120 X 96) END XO
8. LC-PG50 (108 X 96) END XO




9. LC-PG25 (78 X 100) END XO
10. LC-PG25 (84 X 120) END XO
11. LC-PG35 (108 X 96) END XO
12. LC-PG40 (96 X 96) END XO




13. LC-PG30 (96 X 120) END XO


**INTERIOR ELEVATIONS**




PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MET.




PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MET.



PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MET.



PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MET.



PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MET.

XO

START DATE: 12/20/23

FINISH DATE: 12/20/23

CHECKED BY: ENGINEERING

SCALE: 3/32"=1'

DWG BY: BSP

QUOTE:

REVISION:

PAGE: 10 OF 10