

NOTE: PLEASE VERIFY ALL HEAD AND SILL HEIGHTS. VPI defines the Rough Opening (RO) as the clear opening after all installation and waterproofing materials are applied. It is critical that the RO is a minimum of 1/2" larger than the net window frame size for nail flange applications. In the event that your VPI product will be installed with strap anchors, the RO must be 1" larger than the net frame size of the window. VPI shall not be responsible for any incorrect RO sizes.



VPI QUALITY WINDOWS
 7420 E. Ferry Ave.
 Spokane, WA 99202
 www.vpiwindows.com

NAIL FIN - NF



SLIDER FIXED

START DATE: 12/20/23

FINISH DATE: 12/20/23

CHECKED BY: ENGINEERING

SCALE: 3/32"=1'


DWG BY: BSP

QUOTE:


REVISION:

PAGE: 10 OF 10


EXTERIOR ELEVATIONS




1. LC-PG35 (84 X 84) END FW
2. LC-PG50 (48 X 72) END FW
3. CW-PG30 (132 X 48) END FW
4. CW-PG40 (108 X 86) END FW
5. CW-PG45 (72 X 96) END FW



6. CW-PG35 (144 X 96) END SH-FW




7. LC-PG35 (82 X 111) END PP-PP
8. LC-PG40 (98 X 96) END 2P-UT




9. LC-PG40 (84 X 120) END 2Hx3V


INTERIOR ELEVATIONS




PICTURE WINDOWS DO NOT MEET EGRESS



PICTURE WINDOWS DO NOT MEET EGRESS



PICTURE WINDOWS DO NOT MEET EGRESS



PICTURE WINDOWS DO NOT MEET EGRESS