
NOTE: PLEASE VERIFY ALL HEAD AND SILL HEIGHTS. VPI defines the Rough Opening (RO) as the clear opening after all installation and waterproofing materials are applied. It is critical that the RO is a minimum of ½" larger than the net window frame size for nail flange applications. In the event that your VPI product will be installed with strap anchors, the RO must be 1" larger than the net frame size of the window. VPI shall not be responsible for any incorrect RO sizes.




NAIL FIN - NF





EXTERIOR ELEVATIONS





2. LC-PG40 (84 X 78) END CHL-AWN_PW
3. LC-PG40 (96 X 102) END CHL-AWN_PW
4. CW-PG30 (60 X 108) END FIRA
5. CW-PG54 (72 X 96) END CHL-AWN_PW
6. LC-PG30 (114 X 92) END PW_CHR-AWN






10. CW-PG40 (108 X 96) END LAIRFIRA




11. CW-PG40 (96 X 84) END PCRI2A-P 12. LC-PG45 (114 X 96) END CPC-AAA 13. LC-PG60 (96 X 86) END CPC-AAA







PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MEET.




PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MEET.




PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MEET.



PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MEET.



PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MEET.



PLEASE CONTACT YOUR OUTSIDE SALES REPRESENTATIVE TO ENSURE YOUR EGRESS NEEDS ARE MEET.

START DATE:	12/20/23
FINISH DATE:	12/20/23
CHECKED BY:	ENGINEERING
SCALE:	3/32"=1'
DWG BY:	BSP
QUOTE:	
REVISION:	
PAGE: 6 OF	10