


NOTE: PLEASE VERIFY ALL HEAD AND SILL HEIGHTS. VPI defines the Rough Opening (RO) as the clear opening after all installation and waterproofing materials are applied. It is critical that the RO is a minimum of 1/2" larger than the net window frame size for nail flange applications. In the event that your VPI product will be installed with strap anchors, the RO must be 1" larger than the net frame size of the window. VPI shall not be responsible for any incorrect RO sizes.



ENVISION NAIL FIN



ENV

START DATE: 12/21/23

FINISH DATE: 12/21/23

CHECKED BY: ENGINEERING

SCALE: 3/32"=1"


DWG BY: BSP

QUOTE:


REVISION:

PAGE: 1 OF 2


EXTERIOR ELEVATIONS




1. CW-PG40 (42 X 120)
ENV HLOS-U HP




2. CW-PG40 (42 X 120)
ENV HJIS-U HP




3. CW-PG40 (96 X 96)
ENV HLOS-GLFX HP



4. CW-PG40 (96 X 96)
ENV HJIS-P HP




5. LC-PG40 (96 X 125.5)
ENV P-HLOSP HP




6. LC-PG40 (96 X 125.5)
ENV P-HJISP HP


INTERIOR ELEVATIONS




32" CLEAR OPENING
MINIMUM WIDTH IS 40"




32" CLEAR OPENING
MINIMUM WIDTH IS 40"




32" CLEAR OPENING MINIMUM
BAR SET IS 39-1/4"



32" CLEAR OPENING MINIMUM
BAR SET IS 39-1/4"



32" CLEAR OPENING MINIMUM
BAR SET IS 39-1/4"



32" CLEAR OPENING MINIMUM
BAR SET IS 39-1/4"